

### IN THE CLAIMS

Please amend the claims as follows:

- 1-8. (Canceled)
9. (Currently Amended) Apparatus having at least ~~two operating states~~ an on state and an off or standby state and comprising:  
one or more earcups;  
means for sensing acoustic energy based on user movement; and  
means, responsive to a perceived absence of the acoustic energy based on user movement, for switching ~~between the operating states~~ the apparatus from the on state to the off or standby state.
10. (Previously Presented) The apparatus of claim 9 wherein the acoustic energy is inaudible.
11. (Canceled)
12. (Currently Amended) The apparatus of claim 9 ~~wherein one of the two operating states is an on state and the other is an off or standby state, and wherein the means for switching is responsive to the sensed condition to switch from the on state to the off or standby state~~ wherein the means for sensing acoustic energy based on user movement comprises a filter having an output coupled to a threshold detector.
13. (Canceled)
14. (Canceled)
15. (Previously Presented) Apparatus having at least two operating states and comprising:  
one or more earcups;  
circuitry for sensing a condition based on user jaw movements or blood movement within a user's head; and

circuitry for changing the operating state of the headset from an on state to an off state in response to a perceived absence of the condition.

16. (Previously Presented) The apparatus of claim 15 wherein the predetermined period of time is at least one minute and the circuitry for changing comprises analog circuitry.

17-20. (Canceled)

21. (Previously Presented) Apparatus comprising:  
one or more earcups;  
an microphone for sensing acoustic energy produced by user movement;  
a timer; for determining whether the acoustic energy is absent for at least a predetermined amount of time; and  
a switch responsive to the timer for switching ANR circuitry from an active state to an inactive state.

22. (Previously Presented) The apparatus of claim 21, wherein the timer comprises:  
a threshold detector; and  
a microprocessor coupled to the threshold detector and to the switch.

23. (Previously Presented) The apparatus of claim 21, wherein the predetermined amount of time is at least one minute.

24. (Previously Presented) A method of operating apparatus including an audio transducer and ANR circuitry, the method comprising:  
determining whether acoustic energy produced by the user has been sensed by the audio transducer; and  
switching at least a portion of the ANR circuitry from an active state to an inactive or standby state in response to a determination that the acoustic energy has not been sensed for at least a predetermined amount of time.

25. (Previously Presented) The method of claim 24, wherein the acoustic energy is inaudible and the predetermined amount of time is at least one minute.
26. (Previously Presented) The method of claim 24, wherein the apparatus includes an ANR driver; and wherein the method further comprises switching the ANR circuitry from the inactive state to the active state in response to sensing deflection of a portion of the ANR driver.
27. (Previously Presented) The method of claim 24, wherein the acoustic energy is produced by user blood flow.
28. (Previously Presented) The method of claim 24, wherein switching at least a portion of the ANR headset from an active state to an inactive state in response to a perceived absence of the condition comprises:  
starting a timer in response to sensing the condition, with the timer configured to expire after measuring the predetermined amount of time; and  
switching at least the portion of the ANR headset from the active state to the inactive state in response to expiration of the timer.
- 29-40. (Canceled)
41. (Currently Amended) Apparatus comprising:  
ANR circuitry;  
an input node for receiving a signal; and ~~bandpass filter responsive to operation of a microphone to provide a first output based on acoustic energy produced by a user of the apparatus; and~~  
means, including a programmable timer and a switch, responsive to the received signal, for switching the ~~switch responsive to the first output to switch~~ ANR circuitry from an active operating state to an inactive operating state.

42. (Previously Presented) The apparatus of claim 41, further comprising a threshold detector responsive to the first output of the bandpass filter to provide a second output, wherein the switch is responsive to the second output.

43. (Canceled)

44. (Currently Amended) The apparatus of claim 41, wherein the timer comprises ~~programmable means~~ a processor for outputting a control signal to the switch after passage of a predetermined amount of time.

45. (Canceled)

46. (Currently Amended) The apparatus of claim 41, wherein the signal is based on acoustic energy produced by a user of the apparatus ~~the acoustic energy produced by the user is based on blood flow.~~

47. (Currently Amended) Apparatus comprising:  
a filter ~~responsive to operation of a microphone~~ to provide a filter output indicative of whether the apparatus is in normal use ~~operating state based on acoustic energy produced by a user of the apparatus;~~  
a threshold detector responsive to the filter output signal to provide a detector output;  
a digital timer responsive to the detector output to start a timing period and responsive to completion of the timing period to produce a control signal; and  
a switch responsive to the control signal to switch ANR circuitry from an active operating state to an inactive operating state.

48. (Currently Amended) The apparatus of claim 47, wherein the filter output signal is based substantially on acoustic energy produced by a user of the apparatus when the user is wearing at least a portion of the apparatus.

49. (Previously Presented) The apparatus of claim 47, wherein the filter comprises analog circuitry that defines a passband of 1-5 Hertz; the threshold detector comprises analog circuitry; the timer comprises a processor; and the switch comprises a transistor.

50. (Currently Amended) The apparatus of claim 47, wherein the filter output is based on acoustic energy produced by the user ~~is based on blood flow~~ user movement.

51. (Currently Amended) Apparatus comprising:  
a switch for switching ANR circuitry from an active operating state to an inactive operating state; and  
~~a timer means, responsive to disengagement of at least a portion of the apparatus with or from a user,~~ cessation of intended usage of the apparatus, for controlling status of the switch, wherein the timer means included a microprocessor.

52. (Currently Amended) The apparatus of claim 51, wherein the timer means ~~comprises programmable means for outputting~~ outputs a control signal to the switch after passage of a predetermined amount of time.

53. (Previously Presented) The apparatus of claim 51, further comprising:  
a bandpass filter responsive to operation of an ANR microphone to provide an output based substantially on acoustic energy produced by the user.

54. (Previously Presented) The apparatus of claim 53, wherein the bandpass filter has a passband of 1-5 Hertz.

55. (Previously Presented) The apparatus of claim 53, wherein the acoustic energy produced by the user is based on blood flow.

56. (Previously Presented) A method of operating ANR circuitry, comprising:

automatically determining whether acoustic signals produced by a user of the ANR circuitry are present within a cavity associated with the circuitry; and  
automatically turning off the ANR circuitry in response to determining that the acoustic signals produced by the user are no longer present.

57. (Previously Presented) The method of claim 56, wherein the acoustic signals produced by the user are based on user blood flow.

58. (Previously Presented) The method of claim 56, wherein automatically determining whether acoustic signals produced by the user are present comprises:  
producing a first output in response to operation of a microphone;  
filtering the first output to produce a filtered output; and  
determining based on magnitude of the filtered output whether the acoustic signals produced by the user are present.

59. (Previously Presented) The method of claim 51, wherein automatically turning off the ANR circuitry in response to determining that the acoustic signals are no longer present, comprises:  
initiating a time measurement in response to an affirmative determination that acoustic signals produced by the user are present; and  
turning off the ANR circuitry in response to the time measurement indicating passage of at least a predetermined amount of time.

60. (Previously Presented) The method of claim 56, wherein the cavity is at least partly defined by an earcup.

61. (New) A method comprising:  
sensing an electrical signal indicative of intended usage of an ANR headset having ANR circuitry;  
in response to sensing the sensing the electrical signal, resetting a digital timer;

in response to the digital timer measuring a predetermined amount of time without resetting, automatically turning off the ANR circuitry.

62. (New) The method of claim 61, wherein automatically turning off the ANR circuitry occurs in response to a perceived absence of an electrical condition indicative of acoustic energy based on user movement.